

Technical Datasheet

tasker® C102 – 2x4,00 mm²

Red & Black Flat Audio Divisible Cable



CATEGORY Flat Divisible Red and Black Cable
APPLICATIONS Speakers and Home Theatre installation

A: Red and Black PVC sheath.
Outer cable dimension 4,20x8,60 (±0,20) mm.

B: Both conductors in O.F.C. Red Copper.
Stranded formation 56x0,30 mm.
Nominal cross section 2x4,00mm².

MARKING tasker® C102 - 2x4,00 mm² – O.F.C. - SPEAKER CABLE
- MADE IN ITALY

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE or PUR.

Cable Properties

Conductor Resistance	4,31 Ω/Km
Max Rated Voltage (Not for Power)	300 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. D / 30.04.26
		Outdoor	Esterno		X	Mobile	Mobile			For production needs, the marking may be different or absent.
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			