

Technical Datasheet

tasker® C100 TN – 2x3,00 mm²

Transparent Divisible Flat Cable



CATEGORY Flexible Audio Cable (See Audio Catalogue)
APPLICATIONS Speaker and Home Theatre installation

- A:** Transparent **PVC** Sheath.
Outer Diam. Ø 3,90x7,70 (±0,20) mm.
- B:** One conductor of O.F.C. tinned copper and one of O.F.C. Red Copper.
Stranded Formation 44x0,30 mm.
Nominal cross section 2x3,00 mm².

MARKING **tasker®** C100 TN - 2x3.00 mm² – O.F.C. SPEAKER CABLE MADE IN ITALY
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.
PRODUCTION

Coductors Properties

Conductor Resistance	5,70 Ω/Km
Operative Voltage (Not for Power)	300 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. C / 15.05.26
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			