

Technical Datasheet **RoHS₃**

tasker® C198 TN – 2x0,50 mm² - Transparent Flat Cable



A

B

CATEGORY Flexible Audio Cable
APPLICATIONS Speaker and Home Theatre installation

A: Transparent **PVC** Sheath.
Outer Dimension 1,90x3,90 (±0,20) mm.

B: One conductor of O.F.C. tinned copper and one of O.F.C. Red Copper.
Stranded Formation 16x0,20 mm.
Nominal cross section 2x0,50 mm².

MARKING **tasker® C198TN 2x0,50 mm² - O.F.C. – SPEAKER CABLE**
– MADE IN ITALY

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.

Conductors Properties

Conductor Resistance	38,00 Ω/Km
Operating Voltage (Not for Power)	300 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 18.05.26
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			