

Technical Datasheet

tasker® TSK1013 – 2x0,75 mm²

Flat Divisible Audio Cable



A

B

CATEGORY Flexible Audio Cable (See Audio Catalogue)
APPLICATIONS Speaker and Home Theatre installation.

A: Black PVC Sheath with red side band.
Outer cable dimension 2,20x4,50 (±0,20) mm.

B: Both Conductors made of O.F.C. Red Copper.
Stranded Formation with very tin elements to guarantee the flexibility.
formation 42x0,15 mm. Nominal cross section 2x0,75 mm².

MARKING Cable not Marked.
CUSTOM This product may be custom produced also in L.S.Z.H. polymer, PE or PUR.
PRODUCTION

Conductors Properties

Conductor Resistance	21,93 Ω/Km
Operative Voltage (Not for Power)	300 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 14.05.26
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			