

Technical Datasheet

tasker® TSK1016 – 2x2,50 mm²

Flat Divisible Audio Cable



CATEGORY Polarized Flat Cable (See Audio Catalogue)

APPLICATIONS Speaker and Home Theatre installation

A: Black PVC Sheath with red side band.
Outer cable dimension 3,65x7,40 (±0,20) mm.

B: Both Conductors made of O.F.C. Red Copper.
Stranded Formation with very tin elements to guarantee the flexibility,
formation 147x0,15 mm. Nominal cross section 2x2,50 mm².

MARKING Cable not marked

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE or PUR.

Cable Properties

Conductor Resistance	6,41 Ω/Km
Operative Voltage (Not for Power)	300 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 14.05.26
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			