

Technical Datasheet

tasker® TSK1044 - 2x2x0,22 mm² Audio Quad Cable



CATEGORY Audio Cable (See Audio Catalogue)
APPLICATIONS Audio quad premade cables

- A:** Night Blue Flame Retardant PVC sheath.
Outer cable diam. Ø 5,20 (±0,10) mm.
- B:** Braided Shielding O.F.C. tinned copper covering 95% + Drain Wire.
- C:** The cores are stranded in a pair with textile waste filler between conductors and wrapped with not woven polyester based tape.
- D:** Cores Insulation with compact XLPE – Diam. Ø 1,10 (±0,10) mm.
One colored transparent-red and one transparent-yellow.
- E:** O.F.C. red copper - formation 28x0,10 mm.
Nom. Cross section 2x2x0,22 mm².

MARKING tasker® TSK1044 2x2x0,22 mm² - Extra Flex Audio Quad Cable – Made in Italy
CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	65 pF/m
Capacity Core/Shield	150 pF/m
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 16.05.26
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			