

## Technical Datasheet



# tasker® T19 – 2x19 AWG - Flexible Loudspeaker Cable



### CATEGORY APPLICATIONS

Flexible Speaker Cable (See Audio Catalogue)  
Loudspeakers and Electronics.

- A:** Black **Soft PVC** Sheath.  
Outer cable Diam. Ø 5,20 (±0,20) mm.
- B:** Core Insulation with **Flame Retardant PVC** sheath,  
colored one Red and one Black.  
Diam. Ø 1,85 (±0,20) mm.
- C:** O.F.C. red copper formation 14x0,25 mm.  
Nom. Cross section 2x19 AWG.

### MARKING CUSTOM PRODUCTION

**tasker®** T19 - 2x19 AWG - O.F.C. - Loudspeaker Cable - Made in Italy  
This product may be custom produced also in **L.S.Z.H.** polymer, **PE**,  
**PUR**, with or without Metallic Armor.

### Cable Properties

|                                      |            |
|--------------------------------------|------------|
| Conductor Resistance                 | 21,93 Ω/Km |
| Operating Voltage<br>(not for power) | 100 V      |
| Operative Temperature                | -15/+70°C  |

|         |   |                       |                   |              |   |                      |                  |              |   |                   |
|---------|---|-----------------------|-------------------|--------------|---|----------------------|------------------|--------------|---|-------------------|
| USE     | X | Indoor                | Interno Edificio  | INSTALLATION | X | Fixed                | Fissa            | INFORMATION  | X | RoHS2 Compliant   |
| Impiego |   | Outdoor Limited       | Esterno Limitato  | Posa         | X | Restricted Mobile    | Mobile Limitata  | Informazioni | X | Ver. B / 30.03.26 |
|         |   | Outdoor               | Esterno           |              | X | Mobile               | Mobile           |              |   |                   |
|         |   | Outdoor Direct Burial | Esterno Interrato |              |   | Mobile in Drag Chain | Mobile in Catena |              |   |                   |