



Technical Datasheet

tasker® T20 – 2x18 AWG - Flexible Loudspeaker Cable



A

B

C

CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Loudspeakers and Electronics.

- A:** Black Soft **PVC** Sheath.
Outer cable Diam. Ø 5,80 (±0,20) mm.
- B:** Core Insulation with **Flame Retardant PVC** sheath,
colored one Red and one Black.
Diam. Ø 2,20 (±0,20) mm.
- C:** O.F.C. red copper formation 17x0,25 mm.
Nom. Cross section 2x18 AWG.

MARKING **tasker® T20 - 2x18 AWG - O.F.C. - Loudspeaker Cable - Made in Italy**
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**,
PRODUCTION **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	18,00 Ω/Km
Operating Voltage (not for power)	100 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 30.03.26
		Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			