

Technical Datasheet



tasker® T21 – 2x16 AWG - Flexible Loudspeaker Cable



A

B

C

CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables

- A:** Black Soft **PVC** Sheath.
Outer cable Diam. Ø 6,40 (±0,20) mm.
- B:** Core Insulation with **Flame Retardant PVC** Sheath,
colored one Red and one Black.
Diam. Ø 2,50 (±0,20) mm.
- C:** O.F.C. red copper formation 28x0,25 mm.
Nom. Cross section 2x16 AWG.

MARKING **tasker®** T21 - 2x16 AWG - O.F.C. - Loudspeaker Cable - Made in Italy
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	12,50 Ω/Km
Operating Voltage (not for power)	100 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 30.05.26
		Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			