

Technical Datasheet



tasker® T25 – 2x12 AWG - Flexible Loudspeaker Cable



CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables. Not for power supply.

- A:** Black soft **PVC** Sheath.
Outer cable Diam. Ø 8,50 (±0,20) mm.
- B:** Core Insulation with **Flame Retardant PVC**, colored one Red and one Black.
Diam. Ø 3,50 (±0,20) mm.
- C:** O.F.C. red copper formation 71x0,25 mm.
Nom. Cross section 2x12 AWG.

MARKING **tasker®** T25 - 2x12 AWG - O.F.C. - Loudspeaker Cable - Made in Italy
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	4,31 Ω/Km
Operating Voltage (not for power)	100 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B /03.03.26
		Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			