

Technical Datasheet



tasker® T29 – 2x8 AWG - Flexible Loudspeaker Cable



A

B

C

CATEGORY Flexible Speaker Cable

APPLICATIONS Professional Loudspeakers and premade cables

- A:** Black Soft **PVC** Sheath.
Outer cable Diam. Ø 11,00 (±0,20) mm.
- B:** Core Insulation with **Flame Retardant PVC**, colored one Red and one Black.
Diam. Ø 4,60 (±0,20) mm.
- C:** O.F.C. red copper formation 94x0,30 mm.
Nom. Cross section 2x8 AWG.

MARKING tasker® T29 - 2x8 AWG - O.F.C. - Loudspeaker Cable - Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	2,39 Ω/Km
Operating Voltage (not for power)	100 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. C / 30.03.26
		Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			