

Technical Datasheet

tasker® C100 – 2x0,35 mm²

Flat Divisible Audio Cable



A

B

CATEGORY Flexible Audio Cable (See Audio Catalogue)
APPLICATIONS Speaker and Home Theatre installation

A: PVC Sheath, available in different colors.
Outer cable dimension 1,90 x 3,90 (±0,20) mm.

B: One conductor made of O.F.C. tinned copper and one of O.F.C. Red Copper. Formation with 0,20 mm wires.
Nominal cross section 2x0,35 mm².

MARKING Cable not marked
CUSTOM This product may be custom produced also in L.S.Z.H. polymer, PE, PUR.
PRODUCTION

Conductors Properties

Conductor Resistance	58,00 Ω/Km
Max Rated Voltage	300 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver.B / 28.09.26
		Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			