

Technical Datasheet

tasker® C100 – 2x0,50 mm²

Flat Divisible Audio Cable



A

B

CATEGORY Flexible Audio Cable (See Audio Catalogue)
APPLICATIONS Speaker and Home Theatre installation

A: PVC Sheath, available in different colors.
Outer cable dimension 2,00 x 4,10 (±0,20) mm.

B: One conductor made of O.F.C. tinned copper and one of O.F.C. Red Copper. Formation with 0,20 mm wires.
Nominal cross section 2x0,50 mm².

MARKING Cable not Marked
CUSTOM This product may be custom produced also in L.S.Z.H. polymer, PE or PUR.
PRODUCTION

Conductors Properties

Conductor Resistance	38,00 Ω/Km
Max Rated Voltage	300 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 28.09.26
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			