

## Technical Datasheet

### tasker® C123 - 1x0,25 mm<sup>2</sup> - Spiral Shielded Cable



| A | B | C | D |
|---|---|---|---|
|---|---|---|---|

**CATEGORY** Spiral Shielded Cables (See Audio Catalogue)

**APPLICATIONS** Sound Reproduction and Electronics

- A:** Black PVC Sheath.  
Outer Diam. Ø 4,50 (±0,20) mm.
- B:** Shielded with O.F.C. red copper spiral covering 100%.
- C:** Core Insulation with Compact PE – Diam. Ø 2,30 (±0,10) mm.
- D:** O.F.C. red copper formation 8x0,20 mm.  
Nom. Cross section 1x0,25 mm<sup>2</sup>.

**MARKING**

**CUSTOM**

**PRODUCTION**

**tasker® C123 – 1x0,25 mm<sup>2</sup> - Spiral Shielded Cable Low Capacity – Made in Italy**

This product may be custom produced also in **LSZH, PE, PUR**,  
with or without Metallic Armor.

#### Cable Properties

|                       |           |
|-----------------------|-----------|
| Conductor Resistance  | 75 Ω/Km   |
| Capacity Core/Shield  | 94 pF/mt  |
| Max Rated Voltage     | 49 V      |
| Operative Temperature | -15/+70°C |

| USE     | X | Indoor                | Interno Edificio  | INSTALLATION | X | Fixed                | Fissa            | INFORMATION  | X | RoHS2 Compliant   |
|---------|---|-----------------------|-------------------|--------------|---|----------------------|------------------|--------------|---|-------------------|
| Impiego |   | Outdoor Limited       | Esterno Limitato  | Posa         | X | Restricted Mobile    | Mobile Limitata  | Informazioni | X | Ver. A / 16.05.16 |
|         |   | Outdoor               | Esterno           |              |   | Mobile               | Mobile           |              |   |                   |
|         |   | Outdoor Direct Burial | Esterno Interrato |              |   | Mobile in Drag Chain | Mobile in Catena |              |   |                   |