

Technical Datasheet

tasker® C275 L.S.Z.H. – 2x1,50 mm²

Flexible Speaker Cable

Halogen Free

FirestoP®

✓RoHS₃



CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables

A: Black **L.S.Z.H.** sheath. Flame Retardant and Halogen Free.
Outdoor Limited. Outer cable Diam. Ø 8,00 (±0,20) mm.
Inner sheath in white **PVC**.

B: Core Insulation with PVC Sheath, colored one Red and one Black.
Diam. Ø: 3,00 (±0,20) mm.

C: O.F.C. red copper formation 48x0,20 mm.
Nom. Cross section 2x1,50 mm².

MARKING **tasker® C275 L.S.Z.H. 2x1,50 mm² – O.F.C. Loudspeaker Cable – Halogen Free - FirestoP® - Made in Italy**

CUSTOM PRODUCTION This product may be custom produced also in **PVC, PE, PUR,** or Metallic Armored.

Cable Properties

Conductor Resistance	12,50 Ω/Km
Operating Voltage (Not for power)	100 V
Operative Temperature	-30/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 16.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			