

Technical Datasheet

tasker® C275 – 2x1,50 mm²

Flexible Double Density Sheath Speaker Cable



CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables

- A:** First **PVC** sheath, available in different color.
Outer cable Ø: 8,00 (±0,20) mm.
- B:** Second **PVC** Sheath with different density.
- C:** Core Insulation in **PVC**, colored one Red and one Black.
Diam. Ø: 3,00 (±0,20) mm.
- D:** O.F.C. red copper formation 48x0,20 mm.
Nom. Cross section 2x1,50 mm².

MARKING **tasker® C275 - 2x1,50 mm² - O.F.C. - Loudspeakers Cable**
- Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	12,50 Ω/Km
Operating Voltage (Not for power)	100 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 16.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			