

Technical Datasheet

tasker® C276 L.S.Z.H. – 2x2,50 mm²

Flexible Loudspeaker Cable



CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables

- A:** Black **L.S.Z.H.** outer sheath. Flame Retardant and Halogen Free.
Outer Diam. Ø 9,00 (±0,20) mm.
Inner sheath in white **PVC**.
- B:** Cores Insulation with **PVC** sheaths colored one Red and one Black.
Diam. Ø 3,50 mm (±0,20) mm.
- C:** O.F.C. red copper formation 80x0,20 mm.
Nom. Cross section 2x2,50 mm².

MARKING **tasker® C276 L.S.Z.H. 2x2.50 mm² – O.F.C. Speaker Cable – Halogen Free - FirestopP® - Made in Italy**

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	6,41 Ω/Km
Operating Voltage (Not for power)	100 V
Operative Temperature	-30/+70°C

USE	X	Indoor	Interno Edificio
Impiego	X	Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Flexible Limited	Flessibilità limitata
		Dynamic (Drag Chain)	Mobile in Catena
		Dynamic (Torsion)	Mobile in Torsione

INFORMATION	X	RoHS3 Compliant
Informazioni	X	Ver. B / 20.05.19