

Technical Datasheet

tasker® C277 L.S.Z.H. – 2x4,00 mm²

Flexible Loudspeaker Cable



A

B

C

CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables

- A:** Black **L.S.Z.H.** polymer Sheath. Outer Diam. Ø 10,80 (±0,20) mm.
Flame Retardant, Halogen Free.
Inner sheath in white **PVC**
- B:** **PVC** core Insulations, colored one Red and one Black.
Diam. Ø 4,20 (±0,20) mm.
- C:** O.F.C. red copper formation 128x0,20 mm.
Nom. Cross section 2x4,00 mm².

MARKING **tasker®** C277 L.S.Z.H. - 2x4,00 mm² – O.F.C. - Loudspeaker Cable –
FirestopP® + Halogen Free – Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **PVC** polymer, **PE**, **PUR**,
with or without Metallic Armor.

Cable Properties

Conductor Resistance	4,31 Ω/Km
Operating Voltage (Not for power)	100 V
Operative Temperature	-30/+70°C

USE	X	Indoor	Interno Edificio
Impiego	X	Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS2 Compliant
Informazioni	X	Ver. A / 15.02.18
		10% measurement tolerance, unless otherwise indicated