

Technical Datasheet

tasker® C277 – 2x4,00 mm²

Flexible Double Density Sheath Speaker Cable



A	B	C	D
---	---	---	---

CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables

- A:** First **PVC** Sheath. Available in different color.
Outer cable Diam. Ø 10,80 (±0,20) mm.
- B:** Second **PVC** Sheath with different density.
- C:** Core Insulation in **PVC**, colored one Red and one Black.
Diam. Ø 4,20 (±0,20) mm.
- D:** O.F.C. red copper formation 120x0,20 mm.
Nom. Cross section 2x4,00 mm².

MARKING **tasker® C277 - 2x4,00 mm² – O.F.C. - Loudspeaker Cable**
– Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	4,31 Ω/Km
Operating Voltage (Not for power)	100 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			