



Technical Datasheet

tasker® C283 CPR Cca – 2x0,22 + 3x1,50 mm² **DMX 110Ω and Power Cable for Fix Installation**



CATEGORY DMX Cable + Power (See News Brochure)
APPLICATIONS Active Digital Audio Cables

A: Black **L.S.Z.H.** sheath. Flame retardant and halogen free.
Outer cable Diam. Ø 14,00 (±0,20) mm.

Digital Audio 110 Ohm Pair:

B: Black **L.S.Z.H.** sheath. Flame retardant and halogen free.
Diam. Ø 4,00 (±0,20) mm.

C: Shielding O.F.C. red copper Spiral covering 100%
+ O.F.C. tinned copper Drain Wire.

D: Core Insulation in Foam PE, colored one Red and one Blue.
Diam. Ø 1,50 (±0,20) mm.

E: O.F.C. tinned copper - formation 28x0,10 mm.
Nom. Cross section 2x0,22 mm².

Power Conductors:

F: Black **L.S.Z.H.** sheath. Flame retardant and halogen free.
Diam. Ø 7,20 (±0,20) mm.

G: Core Insulation with **L.S.Z.H.** colored:
Brown, Blue and Yellow/Green. Diam. Ø 2,60 (±0,20) mm.

H: O.F.C. red copper formation 29x0,25 mm.
Nom. Cross section 3x1,50 mm².

MILAN S.r.l. a socio Unico
Head Office – Export Department
 Viale Europa, 74
 20047 Cusago (MI) Italy
 Tel. +39 02 9039.4556 – 4158
 www.taskercables.com

Ufficio Commerciale e Distribuzione
 Viale Europa, 72 Strada F12
 20047 Cusago (MI) Italy
 Tel. +39 02 9039.0037 – 0059
 www.tasker.it

Capitale Sociale € 100.000,00 i.v.
 Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
 R.E.A. MI 975732 Reg. Imprese MI 178864-5179-14
 PEC: taskerpec@legalmail.it

MARKING

tasker® C283 CPR Cca - 2x0,22 + 3x1,50 mm² - Digital Audio DMX and Power
 Cable AES/EBU 110Ω – CPR – Cca – s1–d2–a3 – FirestoP® - Halogen Free –
 Made in Italy

Cable Properties

Digital Audio Cables Resistance	89,00 Ω/Km
Digital Audio Impedance	110 Ω
Capacity Core/Core	45 pF/m
Capacity Core/Shield	89 pF/m
Power Conductor Resistance	13,30 Ω/Km
Operating Voltage	300 V (not for power)
Min. Bending Radius (fix)	10xO.D.
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 08.01.26
	X	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			