

MILAN S.r.l. a socio Unico

Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione

Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.

Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
R.E.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it

Technical Datasheet

tasker® C129 – 1x0,35 mm²

Unbalanced Microphone Cable



CATEGORY Microphone Cable (See Audio Catalogue)
APPLICATIONS Unbalanced Microphones and Sound Reproduction.

- A:** Black PVC Sheath.
Outer Diam. Ø 5,20 (±0,10) mm.
- B:** O.F.C. tinned copper braid shielding, covering 90%.
- C:** Core Insulation in transparent Compact PE.
Diam. Ø 3,00 (±0,10) mm.
- D:** O.F.C. tinned copper formation 11x0,20 mm.
Nom. Cross section 1x0,35 mm².

MARKING **tasker® C129 - 1x0,35 mm² - O.F.C. - PROFESSIONAL NOISELESS**
Microphone - cable low capacity – Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	58,00 Ω/Km
Capacity Core/Shield	89,00 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 13.10.26
		Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			10% measurement tolerance, unless otherwise indicated