tasker Since 1977 the excellence of Made in Italy

MILAN S.r.l. a socio Unico
Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione
Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
RE.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it

Technical Datasheet
tasker® C196 – 2x0,50 mm²
Balanced Microphone Cable

RoHS 3



A	B	C	D	E

CATEGORY Balanced Microphone Cable (See Audio Catalogue)
APPLICATIONS Premade Audio Cables and Microphones.

A: Transparent **PVC** Sheath.
Outer Diam. Ø 7,00 (±0,20) mm.
B: Braided Shielding O.F.C. tinned copper covering 95%.
C: Second PVC sheath between cores and shielding.
D: Transparent Cores Insulation with compact PE.
Diam. Ø 2,10 (±0,20) mm.
E: One conductor in O.F.C. red copper and one in O.F.C. tinned copper formation 16x0,20 mm – Nom. cross section 2x0,50 mm².

MARKING **tasker®** C196 - 2x0,50 mm² - 20 AWG - O.F.C. - Low Capacitance Supreme Microphone Cable – Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer**, PE, PUR,** with or without Metallic Armor.

Cable Properties

Conductor Resistance	38,00 Ω/Km
Capacity Core/Core	56 pF/m
Capacity Core/Shield	95 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	**X**	Indoor	Interno Edificio
Impiego		Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	**X**	Fixed	Fissa
Posa	**X**	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	**X**	RoHS2 Compliant
Informazioni	**X**	Ver. A / 26.05.17
10% measurement tolerance, unless otherwise indicated		