tasker Since 1977 the excellence of Made in Italy

MILAN S.r.l. a socio Unico
Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione
Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
RE.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it

Technical Datasheet
tasker® C301 – 2x0,22 mm² RoHS3
Double Sheath Low Capacity Balanced Microphone Cable



A	B	C	D	E

CATEGORY Balanced Microphone Cable (See Audio Catalogue)
APPLICATIONS Premade Audio Cables, also for service use on drums and Microphones.

A: First **PVC** Sheath. Available in different color. Outer cable Diam. Ø 6,20 (±0,20) mm.
B: Second **PVC** Sheath with different density. Diam. Ø 3,80 (±0,20) mm.
C: Shielding O.F.C. red copper Spiral covering 100% + O.F.C. tinned copper Drain Wire.
D: The cores are stranded in a pair with a textile filler between conductors. Core Insulation with a compact XLPE, colored one Red and one Transparent. Diam. Ø 1,20 (±0,20) mm.
E: O.F.C. red copper formation 28x0,10 mm. Nom. Cross section 2x0,22 mm².

MARKING **tasker®** C301 - 1x2x0,22 mm² - O.F.C. - Extra Flex Double Sheathed Microphone Cable – Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer**, PE, PUR,** with or without Metallic Armor.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	70 pF/m
Capacity Core/Shield	124 pF/m
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	**X**	Indoor	Interno Edificio
Impiego		Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	**X**	Fixed	Fissa
Posa	**X**	Restricted Mobile	Mobile Limitata
	X	Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	**X**	RoHS2 Compliant
Informazioni	**X**	Ver. A / 16.05.16