tasker Since 1977 the excellence of Made in Italy

MILAN S.r.l. a socio Unico
Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione
Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
RE.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it

Technical Datasheet
tasker® T443 NBR
Multi 12G-SDI Coaxial Cable 75 Ω

RoHS 3



CATEGORY HD-SDI cable (See Video Catalogue)

APPICATIONS HD-SDI video installation and Broadcast over 12Gb/s

A: Black **Nitrile (NBR)** sheath. UV, water, chemical and oil resistant.
Outer Diam. Ø:21,50 (±0,20) mm.

B: Single coaxial Cables sheathed in black **PVC**.
Diam. Ø:6,80 (±0,20) mm.

C: O.F.C. tinned copper braid shielding covering 75%.
Aluminum/pet/aluminum foil tape covering 100%.

D: Core Insulation with Foam Skin PE. Diam. Ø 4,80 (±0,20) mm.

E: O.F.C. Red Copper stranded formation 7x0,40 mm.
Nom. Cross section 4x1x0,80 mm². (18 AWG)

MARKING **tasker®** T443 NBR – 4x(7x0,40/4,80/7,00) - O.F.C. – multi-coaxial 75 ohm - 12G-SDI Cable –Outdoor Use - Made in Italy

NOTE Recommended installation distances are estimated on SMPTE standards, the real maximum lengths depend on the equipment used, assembled connectors and environmental circumstances.

tasker Since 1977 the excellence of Made in Italy

MILAN S.r.l. a socio Unico
Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione
Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
RE.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it

Section A-A'



Cable Properties

Conductor Resistance	21,00 Ω/Km
Velocity of Propagation	80%
Impedance	75 Ω
Min. bending Radius (fix)	8xO.D.
Min. bending Radius (Mobile)	10xO.D.
Operative Temperature	-30/+70°C

Attenuation dB/100 m

50 MHz	4,50
200 MHz	8,60
1000 MHz	19,90
2000 MHz	30,20
3000 MHz	30,40
6000 MHz	51,50

Recommended installation distances

SMPTE Standard	425-4	2081-1	2082-1
	3G-SDI	6G-SDI	12G-SDI
Max Distances (m)	162	111	78

Recommended connectors

Neutrik Code	**tasker Code**	**Use**
NBNC75BUU11	TN465	3G-SDI applications
NBNC75BUU11X	TN466	6-12G-SDI applications

USE	X	Indoor	Interno Edificio	**INSTALLATION**	X	Fixed	Fissa	**INFORMATION**	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	**Posa**	X	Restricted Mobile	Mobile Limitata	**Informazioni**	X	Ver. A / 07.01.26
	X	Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			