

Technical Datasheet

tasker® C256 - 3x0,22 mm² - Special Microphone Cable



CATEGORY Microphone Cable (See Audio Catalogue)
APPLICATIONS Audio e Microphone premade cables

- A:** Black Soft PVC Sheath.
Outer cable Diam. Ø 5,20 (±0,20) mm.
- B:** Braided Shielding in O.F.C. red copper covering 60% + textile waste filler between conductors and wrapped with not woven polyester based tape.
- C:** Cores Insulation with compact PE. Diam. Ø 1,20 (±0,20) mm.
Color Code: White, Yellow, Red.
- D:** Conductors in O.F.C. red copper with stranded formation 7x0,20 mm.
Nom. Cross section 3x0,22 mm².

MARKING tasker® C256 3x0,22 mm² O.F.C. Shielded Audio Cable
CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	66 pF/m
Capacity Core/Shield	113 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			