

Technical Datasheet

tasker® TSK 1172 - 2x0,50 mm²

Alimentation Cable for LED



CATEGORY Cable for Led (See Electronics Catalogue)
APPLICATIONS Electronics and LED alimentation

- A:** White Soft **Flame Retardant PVC** Sheath.
Outer cable Diam. Ø 5,80 (±0,20) mm.
- B:** The cores are stranded in a pair with waste filler between conductors and wrapped with not woven polyester based tape.
Insulation with PVC, colored one Black and one Red.
Core Diam. Ø 1,80 (±0,20) mm.
- C:** O.F.C. red copper stranded formation 16x0.20 mm.
Nom. Cross section 2x0,50 mm².

MARKING tasker® LED CABLE RGB O.F.C. Firestop® - Made in Italy
CUSTOM PRODUCTION This product may be custom produced also in **LSZH, PE, PUR**, with or without Metallic Armor.

Properties

Conductor Resistance	38,00 Ω/Km
Rating Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio
Impiego	X	Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS2 Compliant
Informazioni	X	Ver. A / 26.05.17