

Technical Datasheet

tasker® C705 U.T.P. Cat. 5e

4x2x0,14 mm² - UL/ETL verified Cable



A	B	C	D
---	---	---	---

CATEGORY Data Transmission (See Data Network Catalogue)
APPLICATIONS LAN cabling and patch cord

- A:** Grey PVC Sheath, RAL 7001. Outer cable Diam. Ø 5,70 (±0,20) mm.
B: The four pairs are stranded together.
C: Insulation with PE. Diam. Ø 0,90 (±0,05) mm.
RJ45 plug connector compatible.
Core colors: White – Blue/Blue White-Orange/ Orange,
White Green/Green, White-Brown/Brown.
D: Stranded formation of 7x0,15 mm in O.F.C. Red Copper.
Nom. Cross section 4x2x0,14 mm².

MARKING **tasker® C705 E TYPE CM 4x2x0,14 mm² 60°C (UL) E534440**
ETL VERIFIED TO TIA/EIA-568-B.2 CAT.5e PATCH CABLE U.T.P.
+meter marking

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	138 Ω/Km
Impedance	100 Ω
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. C / 04.11.25
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			10% measurement tolerance, unless otherwise indicated